Technical Data Sheet

2/13/2015

Model: AJA4492AXD

Product Description

Type:	Reciprocating
Application:	HBP - High Back Pressure
Refrigerant:	R-12
Voltage/Frequency:	208-230V ~ 60Hz 200V ~ 50Hz
Version:	N/A

Product Specifications

General

Evaporating Temp. Range:	-6.7°C to 12.8°C (20°F to 55°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	50
Weight Unit of Measure:	LB
Displacement (cc):	25.95
Oil Type:	Synthetic Alkylate
Viscosity (cSt):	32
Oil Charge (cc):	664

Electrical

Voltage Range (50 Hz):	180-220
Voltage Range (60 Hz):	187-254
Locked Rotor Amps (LRA):	41.8
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	7
Max. Continuous Current (MCC in Amps):	10.1
Motor Resistance (Ohm) - Main:	1.62
Motor Resistance (Ohm) - Start:	11.58
Motor Type:	CSIR
Overload Type:	N/A
Relay Type:	N/A

Agency Approval

cURus Recognized